

Construction	Patterned Loop	Gauge	1/10
Yarn Content	Antron® type 6,6 nylon (SCS-EPP-01226, an Environmentally Preferable Product certified by SCS)	Yarn Type	Antron® Legacy™ nylon
Tufted Yarn Weight	28 oz./sq. yd.	Nominal Total Weight	65 oz./sq. yd.
Avg. Yarn Pile Height	.156"	Average Yarn Density	5,990
Primary Back	Polypropylene	Secondary Back	Action Bac™
Pattern Repeat	.250" (W) x .375" (L)	Width	12'6" Wider widths available.
Custom Colors	Min. order: 45 feet. Please allow a 5 ft. overage from 45 to 100 ft., a 5% overage from 100 to 800 ft. and a 3% overage above 800 ft.	Product Collection	TESSILE
Easy Trim™	U.S. Patent No 6,890,615 B2. Atlas' Easy Trim™ feature, marked by a black line, provides a small linear gap allowing the installer to trim both edges back to the pattern without damaging or cutting any of the yarns within the pattern.		
Alternative Backing Systems	This product is available with PERMIAN BAC™*, an acrylic based backing system (min. 100 lineal feet for 12' width), PERMIAN BAC™ MP* (moisture protection), an acrylic-based backing system (min. 360 lineal feet), FIRMA CUSHION BAC™ Polyurethane carpet backing manufactured with THE ENHANCER* Technology and BioCel** (min. 360 lineal feet), ELEMENT CUSHION BAC™ Polyurethane carpet backing (min. 100 lineal feet), FUSION BAC™ Polyurethane carpet backing manufactured with THE ENFORCER* Technology and BioCel** (min. 360 lineal feet), TERRA CUSHION BAC™ Polyurethane carpet backing manufactured with BioCel** (min. 360 lineal feet) and CAMBRIAN BAC™ Polyurethane carpet backing (min. 100 lineal feet). Standard overages apply. *Trademark of Atlas Carpet Mills. **Trademark of Universal Textile Technologies.		
Area Rugs	Area Rugs are available in a variety of shapes, sizes, backings and edge finishes. Please contact your Atlas Sales Associate for more information on the Atlas Area Rug Program.		
Pattern Match & Installation Guidelines	As with all patterned carpets, a perfect match at the seams may not be obtainable. However, a reasonable pattern match may be achieved by qualified and experienced professional installers utilizing power stretching and stay nailing techniques. All seams and cut edges must be sealed with an Atlas approved "premium low-VOC" seam sealer containing UV enhancer. Complete installation instructions are included with each shipment and may also be viewed at www.atlascarpetmills.com.		
General Guidelines	Chair pads are highly recommended under roller casters to preserve appearance and prevent accelerated wear. Walk-off mats are recommended at all entrances to minimize soiling. This carpet is intended only for use as a floor covering. Atlas will not assume any liability when this carpet is used in any other manner.		
Quality Assurance	All certified carpets of Antron® type 6,6 nylon meet strict performance and construction standards of the Invista performance standards program assuring the highest quality carpet. The Antron® type 6,6 nylon polymer provides superior resistance to crushing, matting, stain penetration and wear.		
Soil Retardant	DuraTech®, a patented soil resistance technology, is only available on styles of Antron® type 6,6 nylon.		
Static Control	Antron® type 6,6 nylon carries a limited lifetime antistatic protection warranty not to exceed 3.5kV.		
Flammability Ratings	ASTM E648 Flooring Radiant Panel Test: Class I. ASTM E662 NBS Smoke Chamber Test; < 450 in the Flaming Mode.		
Indoor Air Quality	Certified by the Carpet and Rug Institute and assigned the Green Label Plus certification number GLP4428 .		
NSF-140 Certification	All Atlas broadloom carpets are certified Gold under NSF-140 .		
Environmental	Atlas BROADLOOM, by total weight, contains either 10% post-consumer recycled content or 20% post-industrial recycled content. Atlas uses Antron® Legacy™ nylon which is an Environmentally Preferable Product. For complete details on contributions to LEED, please visit our website at www.atlascarpetmills.com .		
Warranty	Antron® type 6,6 nylon carries a Limited 10-Year Wear Warranty. See written warranties at www.atlascarpetmills.com.		
Additional Information	Pattern lines, inherent in the pattern and construction of this product, which may be visible lengthwise or widthwise, are not considered a manufacturing defect. Watermarking or shading, a pile reversal phenomenon that can occasionally occur in any carpet construction, regardless of fiber type, is not considered a manufacturing defect. The mill reserves the option of making minor modifications in specifications when necessary in order to improve performance and to accommodate changes in material supply or manufacturing processes.		
Trademarks	© INVISTA All Rights Reserved. Antron® and the Antron® family of marks and logos are trademarks of INVISTA. DuraTech® is a registered trademark for soil resistant treatment. Action Bac™ is a trademark of Propex.		
© Copyright	This pattern is protected under federal copyright law and may not be duplicated without Atlas' express written permission.		

Atlas Carpet Mills

Plant, Offices and Showroom:

2200 Saybrook Avenue
 Los Angeles, CA 90040
 (323) 724-9000 (800) 372-6274
 FAX (800) 272-8527 FAX (323) 724-4526

Chicago Showroom:

The Merchandise Mart
 222 Merchandise Mart Plaza, Suite 1082
 Chicago, IL 60654
 (866) 527-9870 FAX (312) 527-9980

New York City Showroom:

New York Design Center
 200 Lexington Ave., Suite 1314
 New York, NY 10016
 (800) 223-0323 FAX (212) 779-7905

Direct Access and Voice Mail: (800) 367-8188 (Ext: 2300 for SAMPLE and ORDER DESK)

www.atlascarpetmills.com